



SN 4319

Technical Details

- Screw Mounted / Can Be Installed With Liquid Nails
- Made of construction grade Anti-Slip Aluminum alloy 6063-T6
- Excellent quality Anodized Aluminum stair edge nosing trim.
- Attractive anodized coating
- Ideal Anti Slip Solution
- 43.5mm wide X 19.5mm height – Standard Profile Length 3 LM
- Factory Cut option available
- Fixed with 4.2mm X 38mm CSK Self Tapping Screws & S6 Fischer Plugs at Every 260mm Intervals





ANTI SLIP STAIR NOSING

SN 5332

Technical Details

- Screw Mounted / Can Be Installed With Liquid Nails
- Made of construction grade Anti-Slip Aluminum alloy 6063-T6 With Rubber Insert
- Excellent quality Anodized Aluminum With Anti Slip Rubber stair edge nosing trim.
- Attractive anodized coating
- Ideal Anti Slip Solution & With Conceal Screws
- 53mm wide X 32mm height – Standard Profile Length 3 LM
- Fixed with 4.2mm X 38mm CSK Self Tapping Screws & S6 Fischer Plugs at Every 260mm Intervals





ANTI SLIP STAIR NOSING

SN 5130

Technical Details

- Screw Mounted / Can Be Installed With Liquid Nails
- Made of construction grade Anti-Slip Aluminum alloy 6063-T6
With Wide Single Non Slip Carborundum self-adhesive tape of 19.5 mm width
- Attractive anodized coating
- Ideal Anti Slip Solution & With Conceal Screws
- 51mm wide X 30mm height – Standard profile length of 3 LM
- Fixed with 4.2mm X 38mm CSK Self Tapping Screws & S6 Fischer Plugs at Every 260mm Intervals

